



SYN Green

An excellent product for the intermediate golfer seeking consistent ball roll for putting and durability for chip shots. It's remarkable stability also makes it an excellent choice for use in Bocce Courts and playground TrampleZones™.

| | |
|------------------------|--|
| SKU | CPITC |
| Grass Zone Yarn/Color | Nylon / Verde |
| Grass Zone Denier | 4,200 / 8 |
| Thatch Zone Yarn/Color | - |
| Thatch Zone Denier | - |
| Grass Zone Yarn Shape | Textured Diamond |
| Finished Pile Height | 7/8" |
| Finished Pile Weight | 53 oz. |
| Backing | 15 / 18 PP 2-Part / 22oz. EnviroLoc™ |
| Tuft Gauge | 3/16" |
| Total Weight | 81 oz. |
| Tuft Bind | > 8 lbs. |
| Permeability | - |
| Features | EnviroLoc™ HeatBlock™ UV Stabilizers |
| Test Data | ASTM Certified F1292, F1951 IPEMA Certified |



Unmatched Lifetime Warranty



EnviroLoc™ Plant-Based Backing



Deluster + UV Protection



Not to scale. For illustration only.

ASK FOR A...



Dave Pelz
SHOTSTOPPER™
Installation System



GreensMaster™
CERTIFIED
Installer



RECOMMENDED USES



GOLF



BOCCE



PLAY





| | | | |
|-----------------------------------|------------------|--|-------------------|
| Primary Yarn Polymer | Nylon | Primary Backing | 15/18 PP 2-Part |
| Yarn Cross Section | Textured Diamond | Coating Type | 22 oz. EnviroLoc™ |
| Standard Color | Verde | PE Yarn Denier / Ends | 4,200 / 8 |
| Fabric Construction | Tufted | Texturized Thatch Denier / Ends | - |
| Second Yarn Polymer Thatch | - | Warranty Period | Limited Lifetime |
| Secondary Yarn Color | - | | |

| Finish Fabric | English System | | ASTM Test |
|-------------------------------------|------------------------------|--------------------|--------------|
| | <i>Nominal Specification</i> | <i>Value</i> | <i>Units</i> |
| Pile Height (Nominal) | 7/8 | inches | D-5823 |
| Face Weight | 53 | oz/yd ² | D-5848 |
| Total Fabric Weight | 81 | oz/yd ² | D-5848 |
| Primary Backing Weight | 6 | oz/yd ² | D-5848 |
| Secondary Coating Weight | 22 | oz/yd ² | D-5848 |
| Tuft Bind | > 8 | lbs. | D-1335 |
| Grab Tear Strength (Average) | > 200 | lbs. | D-5034 |
| Total Yarn Linear Density | 4,200 | Denier | D-1577 |
| Elongation to Break | > 30 | % | D-2256 |
| Yarn Breaking Strength | > 20 | lbs. | D-5793 |
| Machine Gauge | 3/16 | inches | D-5793 |
| Flammability | Passed | - | D-2859 |
| Water Permeability | - | in/hr | D-1551 |
| Fabric Width | 15 | ft | - |